

## MAXIMUS LD 5W-30

Fully Synthetic Engine Oil for Vehicles with Particulate Filter



### Description

A new generation engine oil formulated with synthetic base oils and special additives, and produced for vehicles with emission reduction systems containing DPF and SCR.

### Applications

MAXIMUS LD 5W-30 is intended for use in all light commercial vehicles requiring engine oil at the ACEA C2 performance level and equipped with exhaust systems containing DPF and SCR. Recommended for use in light commercial vehicle fleets in industries such as transportation, construction, mining, and agriculture.

### Benefits

- Protects the engine against wear at high temperatures perfectly thanks to its high thermal stability.
- Ensures high engine performance.
- Averts the negative effects of burning fuel and protects the engine thanks to its superior TBN.
- Extends the life of exhaust emission systems.
- Protects the environment by contributing to low emission production.
- Helps keep the engine clean by reducing deposit and sediment formation.
- Helps to save on fuel.

### Performance

API SP, ACEA C2

### Typical Specifications\*

SAE Viscosity Grade		5W-30
Density, 15 °C, kg/liter	ASTM D4052	0.850
Flash Point, COC, °C	ASTM D92	220
Viscosity, 40 °C, mm <sup>2</sup> /s		68.2
Viscosity, 100 °C, mm <sup>2</sup> /s	ASTM D445	11.50
Viscosity Index	ASTM D2270	163
Pour Point, °C	ASTM D97	-33

\* Values shown may differ between productions.

LD 5W-30

