

ATF DCT

Monograde High Performance Diesel Engine Oil

Description

Petrol Ofisi ATF DCT is an automatic transmission fluid developed to meet the needs of wet DCT type transmission, produced with synthetic base oils and high technological additive package.

Applications

It is used in the following applications:

Audi	VW TL 052 182	Mitsubishi	MZ320065 Dia-Queen SSTF-I
Audi	VW TL 052 529	Nissan	Ford M2C936A
BMW (Getrag)	83 22 2 148 578, 83 22 2 148 579, 83 22 0 440 214, 83 22 2 147 477	Peugeot	Peugeot/Citroën 9734.S2
Citroën	Peugeot/Citroën 9734.S2	Porsche (ZF)	Porsche Oil No. 999.917.080.00
Ford/Getrag	Ford M2C936A	Seat	VW TL 052 182
Mercedes-Benz	MB 236.21(001 989 85 03)	Skoda	VW TL 052 182
		Volkswagen	VW TL 052 182
		Volvo	1161838 1161839

Benefits

- Maximum wear prevention property
- Extended equipment life
- Longer fluid life
- Gasket and oil seal compatibility

Typical Specifications*

Density, 15 °C, kg/liter	ASTM D4052	0,855
Flash Point, COC, °C	ASTM D92	222
Viscosity, 40 °C, mm ² /s	ASTM D445	42
Viscosity, 100 °C, mm ² /s		7,95
Viscosity Index	ASTM D2270	165
Pour Point, °C	ASTM D97	-42

* Values shown may differ between productions.



Petrol Ofisi