

# MAXIMOTO 20W-40

## Four-Stroke Motorcycle Oil

### Description

Engine oil formulated with high performance additives for four-stroke motorcycles.

Protects the engine perfectly by minimizing viscosity change at high temperatures thanks to its technological additives.

### Applications

It may be safely used in four-stroke and high-performance motorcycles in all seasons. It is also suitable for motorcycles manufactured in Europe and Far East where API SN and/or JASO MA2 specifications are recommended.

### Benefits

- Extends engine life by perfectly protecting the engine.
- Ensures high engine power by reducing in-engine friction.
- Prevents tearing of the oil film by keeping the viscosity of the oil under control even under severe conditions thanks to its high viscosity index.
- Ensures excellent engine performance at high temperatures in air-cooled and water-cooled engines.

### Performance

API SN, JASO MA2

### Typical Specifications\*

SAE Viscosity Grade		20W-40
Density, 15 °C, kg/liter	ASTM D4052	0,872
Flash Point, COC, °C	ASTM D92	257
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D445	135,9
Viscosity, 100 °C, mm <sup>2</sup> /s		15.47
Viscosity Index	ASTM D2270	118
Pour Point, °C	ASTM D97	-21

\* Values shown may differ between productions.

